



**NOW AVAILABLE FOR EASY  
ON-LINE ORDERING AT:**

[www.KF7P.com](http://www.KF7P.com)

**OR BY PHONE:  
801-231-2658**

# ZIP POWER CORDS

*Each of our 2 Conductor Zip Power Cords are manufactured with a high quality, flexible PVC insulation, which is ideal for both AC and DC power applications.*

*Each of the Zip Power Cords work with standard power pole, banana, screw type, or crimp type terminals.*

*Use the chart below to find the appropriate power cord that will carry the amount of current your system is designed to handle.*

*Should you need additional information, please give us a call at any time.*



## **P/N: ZIP-0802-RB**

**CONDUCTORS: 8 AWG 152/30 BARE COPPER**  
**INSULATION THICKNESS: .030"**  
**DIMENSIONS: .460" X .225"**  
**VOLTAGE: 300 V**  
**CURRENT: 65 AMPS**

## **P/N: ZIP-1002-RB**

**CONDUCTORS: 10 AWG 105/30 BARE COPPER**  
**INSULATION THICKNESS: .030"**  
**DIMENSIONS: .381" X .190"**  
**VOLTAGE: 300 V**  
**CURRENT: 47 AMPS**

## **P/N: ZIP-1202-RB**

**CONDUCTORS: 12 AWG 65/30 BARE COPPER**  
**INSULATION THICKNESS: .030"**  
**DIMENSIONS: .335" X .160"**  
**VOLTAGE: 300 V**  
**CURRENT: 36 AMPS**

## **P/N: ZIP-1402-RB**

**CONDUCTORS: 14 AWG 41/30 BARE COPPER**  
**INSULATION THICKNESS: .025"**  
**DIMENSIONS: .255" X .120"**  
**VOLTAGE: 300 V**  
**CURRENT: 27 AMPS**

## **P/N: ZIP-1602-RB**

**CONDUCTORS: 16 AWG 26/30 BARE COPPER**  
**INSULATION THICKNESS: .025"**  
**DIMENSIONS: .235" X .110"**  
**VOLTAGE: 300 V**  
**CURRENT: 19 AMPS**

## **P/N: ZIP-1802-RB**

**CONDUCTORS: 18 AWG 16/30 BARE COPPER**  
**INSULATION THICKNESS: .025"**  
**DIMENSIONS: .215" X .100"**  
**VOLTAGE: 300 V**  
**CURRENT: 15 AMPS**